



# **Nodolini**

---

## **SPRINKLERS**



**S70 - 25° C.W.**

**S70 SUPER - 25° C.W.**

# S70 - 25° C.W.

## S70 SUPER - 25° C.W.

**Sprinklers for CORROSIVE WATERS, WASTEWATERS, SEAWATERS,  
CORROSIVE LIQUIDS, CORROSIVE ENVIRONMENTS**

- Mechanical parts are internal and protected against harsh environments and corrosive waters
- Aluminium parts are treated with anodic oxidation, plastic coating and cataphoresis
- All the screws, nuts, washers and pins are in stainless-steel 304
- Nozzles are made in special bronze (NODOLINI-ALLOY)
- Irrigators can be used with HIGH PRESSURE (1500 kPa)
- Personalized solutions are possible, such a stainless-steel nozzles
- Model S70-25°-C.W. NODOLINI flange connection
- Model S70 SUPER-25°-C.W EUROFLANGE connection (inlet diameter 80 mm)

### **TECHNICAL DATA**

Nozzle Ø mm	Pressure atm.	Discharge l/min	Length of jet m
24	4,0 - 5,0 - 6,0	729 - 815 - 893	45 - 52 - 55
26	4,0 - 5,0 - 6,0	856 - 957 - 1048	47 - 53 - 57
28	4,0 - 5,0 - 6,0	992 - 1109 - 1215	49 - 54 - 59
30	5,0 - 6,0 - 7,0	1272 - 1393 - 1505	55 - 61 - 63
32	5,0 - 6,0 - 7,0	1449 - 1587 - 1714	57 - 63 - 66
34	6,0 - 7,0 - 8,0	1792 - 1935 - 2069	64 - 67 - 69
36	6,0 - 7,0 - 8,0	2009 - 2170 - 2320	65 - 69 - 71
38	7,0 - 8,0 - 9,0	2418 - 2585 - 2742	71 - 73 - 75

I dati tecnici sono orientativi e non impegnativi  
*The technical characteristics are indicative and not binding*

**C.W. line of sprinklers for corrosive waters**



**Nodolini**  
SPRINKLERS

**NODOLINI SPRINKLERS**  
42045 LUZZARA (RE) ITALY  
info@nodolini.com www.nodolini.com